

DATA SHEET



Technical Data Sheet

CLEARPAQ 4558 (Plastick 101)

Introduction:

Clearpaq 4558 is a Polystyrene adhesive – medium drying, with low viscosity and low flammability.

Safety:

IMPORTANT: Before embarking on any work involving **Clearpaq 4558**, the Safety Data Sheet should be carefully studied by those carrying out the work.

Method of Use:

Ensure that the surfaces to be bonded are clean & dry.

Apply an even coat of **Clearpaq 4558** adhesive to one surface only and bond immediately with pressure. Allow to stand for at least 24 hours to complete bond formation.

Shelf life

Clearpaq 4558 in an unopened container has a shelf life of 6 months.

Always replace the lid of the container immediately after use to prevent evaporation of the solvent.

Packaging:

For current pack sizes, please contact our Customer Service Department.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for loss or damage that may result from the use of the information, due to the responsibility of variations of processing or working conditions and/or workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.

<u>Adhesive Type</u> Synthetic
<u>Solids</u> 34% approx
<u>Viscosity</u> 2,500 mPa.s approx.
<u>Specific Gravity</u> 0.9 approx.
<u>Cleaner</u> No. 7
<u>Storage</u> 5 – 25°C
<u>Shelf Life</u> 6 Months